



Product Ref: PRO-700 – Disposable Nitrile Gloves. Single use

Sizes available: XS (6), S (7), M (8), L (9) and XL (10)

A Declaration of Conformity can be downloaded from the following link: www.treadstoneproducts.com/treadstone-safety/product/PRO-700

These products are classed as Personal Protective Equipment (PPE) by the European PPE Regulation (EU) 2016/425 and have been shown to comply with this Regulation through the Harmonized European Standards BS EN 420:2003+A1:2009, EN ISO 374-1:2016 and EN ISO 374-5:2016, EN 455-1:2000, EN 455-2:2015, EN 455-3:2015 and EN 1186-1:2002. The gloves fulfil all requirements for EU type-examination for PPE and are subject to the conformity assessment procedure (Module C2).

Manufacturer:

Treadstone Products
Unit 36, Abenbury Way,
Wrexham Industrial Estate
Wrexham, UK, LL13 9UZ
Tel: +44(0) 1978 664667
E-mail: info@treadstoneproducts.com
www.treadstoneproducts.com


Product made in China

Notified Body:

SATRA Technology Europe Ltd
Bracetown Business Park
Clonee
DUBLIN
D15 YN2P
Ireland
Tel: +353 (1) 437 2484
email: info@satra.com
www.satraeurope.com
(Notified Body: 2777)

Use

Protective gloves against chemicals and micro-organisms for a limited period of time. These gloves have been tested and certified against BS EN 420:2003+A1:2009, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 455-1:2000, EN 455-2:2015, EN 455-3:2015 and EN 1186-1:2002 indicated by the markings applied to the glove packaging and shown below, in accordance with the PPE Regulation (EU) 2016/425. The gloves should therefore only be used for protection against the specific risks identified by the pictograms and test results below. Performance can be significantly affected by chemical concentration, temperature and mixture.



Explanation of pictograms:



Please read this user information sheet before using the gloves. Further information is available from the Manufacturer details above.



ISO 374-1:2016 – Protective gloves against dangerous chemicals and micro-organisms – Part 1: Terminology and performance requirements for chemical risks

K = Sodium hydroxide 40%. CAS number: 1310-73-2. Class: Inorganic base. Permeation level 6/ Degradation level 38.4%

T = Formaldehyde 37%. CAS number: 50-00-0. Class: Aldehyde. Permeation level 5/ Degradation level 46.6%

P = Hydrogen peroxide 30%. CAS number: 7722-84-1. Class: Peroxide. Permeation level 2/ Degradation level 17.6%

EN 374-4: 2013 Degradation results indicate the change in puncture resistance of the gloves after exposure to the challenge chemical

Each combination of protective glove/test chemical shall be classified according to Table 1 below, using the results as given in EN 16523-1:2015, 8.5.1.1 or 8.5.1.3 for the normalized breakthrough time. For Type B gloves, the permeation performance shall be at least level 2 against minimum of three test chemicals listed in Table 2 overleaf.

Table 1 — Permeation performance levels

Measured breakthrough time min	Permeation performance level
>10	1
>30	2
>60	3
>120	4
>240	5
>480	6

Classification	Chemical breakthrough time
Type A	>30 minutes against at least 6 chemicals from Table 2
Type B	>30 minutes against at least 3 chemicals from Table 2
Type C	>10 minutes against at least one chemical from Table 2 (no code below the pictogram)

Table 2 — List of test chemicals

CODE LETTER	CHEMICAL	CAS NUMBER	CLASS
A	Methanol	67-56-1	Primary alcohol
B	Acetone	67-64-1	Ketone
C	Acetonitrile	75-05-8	Nitrile compound
D	Dichloromethane	75-09-2	Chlorinated hydrocarbon
E	Carbon disulphide	75-15-0	Sulphur containing organic compound
F	Toluene	108-88-3	Aromatic hydrocarbon
G	Diethylamine	109-89-7	Amine
H	Tetrahydrofuran	109-99-9	Heterocyclic and ether compound
I	Ethyl acetate	141-78-6	Ester
J	n-Heptane	142-82-5	Saturated hydrocarbon
K	Sodium hydroxide 40 %	1310-73-2	Inorganic base
L	Sulphuric acid 96 %	7664-93-9	Inorganic mineral acid, oxidizing
M	Nitric acid 65 %	7697-37-2	Inorganic mineral acid, oxidizing
N	Acetic acid 99 %	64-19-7	Organic acid
O	Ammonium hydroxide 25 %	1336-21-6	Organic base
P	Hydrogen peroxide 30 %	7722-84-1	Peroxide
S	Hydrofluoric acid 40 %	7664-39-3	Inorganic mineral acid
T	Formaldehyde 37 %	50-00-0	Aldehyde

BS EN 374-2:2014– Protective gloves against dangerous chemicals and micro-organisms – Part 2: Determination of resistance to penetration
 Gloves have passed the tests for air leak and water leak in accordance with EN ISO 374-2:2014



ISO 374-5:2016 – Protective gloves against dangerous chemicals and micro-organisms – Part 5: Terminology and performance requirements for micro-organisms risks

Gloves comply with the requirements given in EN 420:2009, Clause 4, Clause 5 and Clause 7, and meet the requirements of EN ISO 374-5 :2016 for resistance to penetration by blood-borne pathogens-test method using Phi-X174 bacteriophage.

WARNING! This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals. The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the cuff is tested also) and relates only to the chemical tested. It can be different if the chemical is used in a mixture. It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation. When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. Testing details are available upon request using the contact information shown above.

Precautions for use

1. These gloves are designed for single use only – do not re-use.
2. Protection is limited to part of the hand only.
3. Before usage, inspect the gloves for any defect or imperfections (e.g. cuts or holes). Do not use damaged gloves. If in doubt, do not use the gloves.
4. Do not use where there is a risk of entanglement.
5. Do not use near a naked flame or sources of extreme heat.
6. Not suitable for protection against ionising radiation.
7. Not for use in explosive environments.
8. The gloves should only be used for splash protection of, or short contact with, chemicals.
9. Ensure that chemicals cannot enter via the cuff and that no chemicals come into contact with the skin, even if they are assumed to be harmless.
10. Before removal, gloves should be cleaned of any contamination.
11. Do not reverse the gloves.
12. The gloves have not been tested against mechanical or thermal risk, and should not be used in applications which require protection against these risks.

Ingredients / Hazardous Ingredients

Some gloves may contain ingredients, which could potentially cause irritation / allergic reaction. In case of any adverse reaction / irritation, seek medical advice.

Care instructions

Storage: When not in use, store the product in a dry place away from direct sunlight, sources of contamination and extremes of temperature.

Cleaning: These gloves are not suitable for washing. Do not launder or wash.

Disposal

Dispose of used gloves in accordance with Local Authority guidelines.

Retain these instructions for future reference.