

USER INSTRUCTIONS



Product Ref: PRO-940 - 15 Gauge seamless recycled polyester liner, Double dipped, smooth and sandy nitrile, thumb crotch Sizes available: 8, 9, 10 and 11

These products are classed as Personal Protective Equipment (PPE) and comply with the

EU Regulation 2016/425 on personal protective equipment. They have been shown to comply with these Regulations through the Standards BS EN 388:2016+A1 2018, and BS EN ISO

21420:2020

Manufacturer:

The Goodlife Outdoor Company Ltd
T/A Treadstone Products,
12 Rossett Park,
Darland Lane,
Wrexham,
Wales,
LL12 0FB
Tel: +44(0) 1978 664667
info@treadstoneproducts.com

Notified Body: 2474

MIRTA-KONTROL d.o.o.
Javorinska 3
HR-10040 Zagreb-Dubrava Croatia
00 385 1 24 31 346
00 385 1 24 31 347
cert@mirta-kontrol.hr
www.mirta-kontrol.hr


Instructions for use

Donning / Doffing: To put the glove on pull over the top of the hand inserting finger and thumb in to the applicable pouch. To remove pull away from the top of the finger. **Care:** Before removal, gloves should be cleared of any contamination. **Storage:** When not in use, store the product in a dry place away from direct sunlight, sources of contamination and extremes of temperature. **Handling:** New and used gloves should be thoroughly checked for signs of wear or damage (e.g. cuts or holes) before use. Do not use damaged gloves.

Performance and limitation of use – This product has been tested in accordance with:


BS EN 388:2016+A1:2018, BS EN ISO 21420:2020 (See table below) BS EN ISO 21420:2020: **Dexterity level 3**

BS EN 388:2016+A1 201

Tested in accordance with EN 388 :2016 +A1 2018	Requirement	Level
 4 1 3 1 X	(6.1) Abrasion resistance	4
	(6.2) Blade cut resistance	1
	(6.4) Tear resistance	3
	(6.5) Puncture resistance	1
	(6.3) TDM Cut resistance	X
	(6.6) Impact protection	

X: indicates that the glove has not been tested

EN 388:2016+A1:2018



EN 388:2016+A1:2018 Levels are based on the table below:

TEST	LEVEL 1	LEVEL 2	LEVEL 3	LEVEL 4	LEVEL 5	
6.1 Abrasion resistance (number of rubs)	100	500	2000	8000	-	
6.2 Coupe test: Blade cut resistance (index) ^{1,2}	1.2	2.5	5.0	10.0	20.0	
6.4 Tear resistance (N)	10	25	50	75	-	
6.5 Puncture resistance (N) ³	20	60	100	150	-	
Levels of performance for materials tested with EN ISO 13997						
TEST	LEVEL A	LEVEL B	LEVEL C	LEVEL D	LEVEL E	LEVEL F
6.3 TDM: cut resistance (N) ^{1,2}	2	5	10	15	22	30
Levels of performance tested according to EN 13594:2015, 6.9 with impact energy of 5 J						
TEST	PASS	NOT TESTED / FAIL				
Impact protection ⁴	P	<BLANK> - No code or text is added if not tested or test failed				

Test results relate to the palm area of the glove unless otherwise stated

NOTE 1: For dulling during the cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

NOTE 2: There is no correlation between the levels of performance obtained with the 6.2 and 6.3 test methods.

NOTE 3: Gloves meeting the requirements for resistance to puncture may NOT be suitable for protection against sharply pointed objects such as hypodermic needles.

NOTE 4: Each area where impact protection is claimed shall be tested. Due to the test method (test specimen dimensions), protection against impacts on fingers cannot be tested. When the requirements of the impact test are fulfilled by the gloves, the marking code 'P' is added after the five performance levels number, otherwise no code is added.

Notes:

- (a) Gloves are made from recycled polyester, dipped with nitrile sandy coating
- (b) Gloves are designated for protection against mechanical risks. Cat II Intermediate risk only. See performance data.
- (c) Not suitable for use where there is a risk of entanglement (for example near moving machinery), chemical risk or electrical risk.
- (d) These gloves are not suitable for washing. Do not launder or wash. Gloves can be cleaned using a damp cloth or similar.
- (e) Some gloves may contain ingredients, such as natural rubber latex and accelerators which could potentially cause irritation / allergic reaction. In case of any adverse reaction / irritation, seek medical advice.
- (f) Retain these instructions for future reference. (g) Gloves protect part of the hand only



For further information, user instructions, DofC or details of our full range scan QR code or go to:
<https://www.treadstoneproducts.com/treadstone-safety/>

Product made in China