



**SAFETY**  
WITHOUT COMPROMISE

PRO-330

PRO

Aramid



## DATA SHEET

**TREADSTONE**

SAFETY



### Product Description

Special non linting Para Aramid, 7 gauge for thickness, comfort and 100°C heat protection. A superb glove for multi-hazard use where cut risk and heat combine. Provides added cut resistance, improved contact heat resistance and even additional warmth where thermal cold resistance might be required. Excellent dexterity and full breathability. EN388:2016 Cut level C. EN 407 contact heat resistant up to 100°C.

### Key Features

Superb dry handling. Excellent abrasion resistance. Cut level C. 100°C contact heat rating. Improved heat resistance properties compared to standard HPPE fibres, providing enhanced degradation resistance at high temperatures.

### Applications

Dry handling where enhanced cut and heat resistance are required, such as mechanical, engineering, manufacturing, automotive, metal parts handling, maintenance, construction, HVAC and assembly work.

### Product Information

#### Materials:

Coating - Plain Glove, no coating. Knitted.  
Liner - Seamless 7 gauge Aramid Non Linting  
Wrist - Elasticated Cuff  
Cuff binding- Polyester  
Size- Treadstone Colour Coded System  
Spectrum-iD- N/A

### Size


### Code

### Case Quantity

|    |            |
|----|------------|
| 8  | PRO-330/08 |
| 9  | PRO-330/09 |
| 10 | PRO-330/10 |
| 11 | PRO-330/11 |

Colour inner box of 20 pairs  
Outer shipper 120 pairs

### Certification



|                                       |                                          |       |
|---------------------------------------|------------------------------------------|-------|
| EN 407:2020                           |                                          |       |
| Tested in accordance with EN 407:2020 |                                          |       |
|                                       | Requirement                              | Level |
|                                       | (4.5.2) Limited flame spread             | X     |
|                                       | (4.5.3) Contact heat                     | 1     |
|                                       | (4.5.4) Convective heat                  | X     |
|                                       | (4.5.5) Radiant heat                     | X     |
|                                       | (4.5.6) Small splashes of molten metal   | X     |
| X 1 X X X X                           | (4.5.7) Large quantities of molten metal | X     |

**TREADSTONE**  
SAFETY  
Treadstone Products  
LLI2 0FB, UK  
CODE: PRO-330/09  
SIZE: 9  
Mfg No: 1889



www.treadstoneproducts.com

CE Certificate number: UE-001040/00

Notified Body: Eurofins Textile Testing Spain, S.L. U/German Bernacer, 403203 Elche (Alicante) Spain No. 2865

[www.eurofins.co.uk](http://www.eurofins.co.uk)

### About Treadstone

#### Who are we?

Treadstone Products is the European face of one of China's finest glove manufacturers - Jiangsu CLS Technology. Our glove portfolio is produced almost entirely in our own exceptional, modern yarn and coating facilities, alongside our superb research centre. Our current capacity is in excess of 1.2 billion pairs of gloves per annum. Our products are all made to the highest quality, meeting the latest EN and ANSI Standards. Our factory has ISO 9001 quality management, ISO 14001 Environmental Management, SA8000 Social Accountability and C-TPAT Management certificated systems in place.

Treadstone represents a new and dynamic, modern range of high quality safety products for discerning glove users and safety conscious employers across Europe. We're building a name and a brand that will be a beacon of trust, with a service and support system to match.

*Safety, without compromise.*

Treadstone Products  
12 Rossett Park, Darland  
Lane, Wrexham, Wales,  
LLI2 0FB

Tel: +44 (0)1978 664 667  
Fax: +44 (0)1978 664 634  
[treadstoneproducts.com](http://treadstoneproducts.com)  
[info@treadstoneproducts.com](mailto:info@treadstoneproducts.com)



For further  
information, user  
instructions or  
details of our full  
range, scan here:

